

เครื่องขันทอร์คไฟฟ้า

ขันน็อตขนาดใหญ่ ด้วยพลังงานไฟฟ้า ไม่เสียแรงขัน
เพียงแค่ปลายนิ้วกด ใช้เวลาเพียงสั้นๆ แต่ได้แรงบิดสูง

**Compact Body!
Light Weight!
High Power!**



GNR, GNRS SERIES เครื่องขันทอร์คไฟฟ้า NUTRUNNER

Item No.	GNR32E-CE	GNR52E-CE	GNR82E-CE	GNR122E-CE	GNR212E-CE	GNRS402E-CE
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Rated Voltage(Single Phase)	220-230V	220-230V	220-230V	220-230V	220-230V	220-230V
Max. Current	5.5A	7.5A	7.5A	9A	9A	9A
Rated Input Power	1150W(2s/3s)	1650W(2s/3s)	1650W(2s/3s)	1900W(2s/3s)	1900W(2s/3s)	1900W(2s/3s)
Rated Max. Torque	300 Nm.	500 Nm.	800 Nm.	1200 Nm.	2100 Nm.	4000 Nm.
Repeated Accuracy	±5%	±5%	±5%	±5%	±5%	±5%
Controllable Torque Range	150~300 Nm.	200~500 Nm.	350~800 Nm.	500~1200 Nm.	1000~2100 Nm.	1600~4000 Nm.
No-Load Speed	35 min ⁻¹ (rpm)	29 min ⁻¹ (rpm)	19 min ⁻¹ (rpm)	16 min ⁻¹ (rpm)	8 min ⁻¹ (rpm)	4 min ⁻¹ (rpm)
Noise&Vibration Level	Sound Pressure Level 86dB(A) Sound Power Level 97dB(A) Vibration Level Less than 2.5 m/s ²			Sound Pressure Level 84dB(A) Sound Power Level 95dB(A) Vibration Level Less than 2.5 m/s ²		
Weight (Main Body)	4.5 kg.	5.0 kg.	5.4 kg.	7.3 kg.	8.8 kg.	9.0 kg.